

# Specification: S5



# Defibrillator/ Monitor

## S5



### Standard Configuration:

Manual defibrillation, AED, Pacer, 3/5-lead ECG, RESP, Thermal Recorder

### Optional:

NIBP, PR, SpO<sub>2</sub>, EtCO<sub>2</sub>(Specific parameters refer to CO<sub>2</sub> module parameter table)

### Physical Characteristics

Size: 295mm×252mm×316mm  
Weight: 5.6kg (Including 1 battery);5.384(Main unit)  
Screen Size: 7" TFT screen  
Resolution: 800 × 480  
Waveforms: Max 4 waveforms

### Operation Environment

Temperature: 0~45°C  
Humidity: 10%~95%, non-condensation  
Atmosphere Pressure: 700hPa~1060hPa  
Ingress Protection: IP44  
Power requirement: 100-240V~, 50/60Hz±3Hz  
Battery type: Rechargeable Lithium-ion battery  
Battery capacity: 7500mAh, d.c.14.8V  
5000mAh, d.c.14.8V  
Battery number: 1  
Battery recharging Time: 7500mAh Battery: Less than 2 hours to 80% and less than 3 hours to 100% with equipment power off  
5000mAh Battery: Less than 1.5 hours to 80% and less than 2.5 hours to 100% with equipment power off  
Battery backup: 7500mAh Battery: Monitoring Mode: no less than 6 hours  
Defib Mode: 210 times (360J charge at intervals of 1minute without recording);

Pacing Mode: 4.5 hours (Load:50 Ω , frequency: 80bpm, current: 60mA, without recording)  
5000mAh Battery:  
Monitoring Mode: no less than 4 hours  
Defib Mode: 120times (360J charge at intervals of 1minute without recording);  
Pacing Mode: 3hours (Load:50 Ω , frequency: 80bpm, current: 60mA, without recording)  
Manual from X to 100, X refers to the darkest brightness (X is 10 by default)

Brightness:

### Indicator

Two alarm indicators  
Power indicator  
Battery indicator  
Maintain indicator  
QRS beep and alarm sound  
Operating key sound

### Interfacing

USB interface  
RJ45 interface  
AC power input  
Multi-functional connector

### Date storage

Alarm Event: 200 groups  
Patient profiles: 100 groups  
Patient Events: 1000 groups  
Wave Review: 10min  
NIBP Review: 2000 groups  
Trend Graph: 160 hours  
Trend Table: 160 hours  
Voice recording: Max 240 min in total;

Marked events	(Up to 60 min for each patient) Available
Power-off storage:	Yes
Alarm:	User-adjustable High and Low 3-level Limits; Prioritized audible and visual alarm
Network:	Connected to Central Monitoring System by hardwire/wireless

## Recorder

Type:	Built-in; Thermal array
Channel:	Max 3 channel waveforms
Real-time recording:	3s, 5s, 8s, 16s, 32s, Continual
Speed:	6.25mm/s, 12.5mm/s, 25mm/s, 50mm/s
Record width:	50mm
Resolution:	8dot/mm (Horizontal and vertical)
Background grid:	Configurable
External printer:	Yes

## Defibrillation

Operating mode:	Manual Mode, AED Mode, , Synchronous Defibrillation
Waveform:	Biphasic truncated exponential waveform, with impedance compensation
Defibrillation pathway:	External defibrillation
Electrode type:	External defibrillation paddles, multifunctional electrode
External defibrillation electrode paddles:	Supports charging, discharging and energy selection; Charging completion indicator
Charge Time: (Battery power)	Less than 3 seconds to 200 Joules with a new, fully charged battery Less than 7 seconds to 360 Joules with a new, fully charged battery
Charge Time: (AC power)	Less than 4 seconds to 200 Joules; Less than 8 seconds to 360 Joules
Energy accuracy:	±1.5J or ±10% of setting, whichever is greater, while 50 Ω impedance ±2J or 15% of setting, whichever is greater, while 25 Ω, 75 Ω, 100 Ω, 125 Ω, 150 Ω, 175 Ω impedance
Patient Impedance Range:	20~300 Ω (External defibrillation);

Defibrillation proof:	Type CF: ECG, RESP, SpO <sub>2</sub> , NIBP, PR; Type BF: EtCO <sub>2</sub>
-----------------------	--

## Manual Mode

External defibrillators:	1J~360J, 25 types (1/2/3/4/5/6/7/8/9/10/15/20/30/50/70/100/120/150/170/200/220/250/270/300/360J)
Synchronous Cardioversion:	Energy transfer begins within 60ms of the R wave from internal Sync signal Energy transfer begins within 25ms of the External Sync signal

## AED

Output Energy:	Adujustable:100-360J
Number of electric shocks	Adjustable: once, twice, 3 times
Types can be AED:	VF & VT
AED maximum time required for cardiac rhythm analysis to be ready for discharge:	Battery power supply: 18s AC power supply: 21s

## Noninvasive Pacing

Waveform:	Monophasic square wave pulse
Pulse Width:	20ms or 40ms
Accuracy:	±5%
Pacing Mode:	On-demand or fixed
Pacing frequency:	30 ppm to 210 ppm
Accuracy:	±1ppm or ±1.5% (whichever is greater)
Pacing output:	0 mA to 200 mA
Accuracy:	±5% or ±5mA, whichever is greater
Speed-down pacing:	Pacing pulse frequency reduced to 25% of original value.

## ECG (leads)

Lead Type:	3 leads ECG, 5 leads ECG, AUTO
Lead selection:	5-lead: I; II; III; aVR; aVL; aVF; V 3-lead: I; II; III
Multi-lead synchronization analysis:	Available
ECG wave gain:	Auto, 1.25 mm/mV (×0.125), 2.5 mm/mV (×0.25), 5 mm/mV (×0.5), 10 mm/mV (×1), 20 mm/mV (×2), 40 mm/mV (×4),
Accuracy:	Less than ±5%



Sweep speed: 6.25 mm/s, 12.5 mm/s, 25 mm/s, 50 mm/s

Accuracy: Less than  $\pm 10\%$

Heart Rate: Adult: 15~300bpm  
Pediatric: 15~350bpm  
Accuracy:  $\pm 1$ bpm or  $\pm 1\%$ (whichever is greater)

Alarm limit range  
Adult:  
High limit: (low limit+2bpm) ~ 300bpm  
Low limit: 15bpm~ (high limit-2bpm)  
Pediatric:  
High limit:(low limit+2bpm) ~ 350bpm  
Low limit: 15bpm~(high limit-2bpm)

Resolution: 1 bpm

Accuracy:  $\pm 1$ bpm

Bandwidth: Monitoring: 0.5~40Hz (-3.0dB~+0.4dB)  
Diagnosis: 0.05~150Hz (-3.0dB~+0.4dB)  
Surgery: 1~20Hz (-3.0dB~+0.4dB)  
ST: 0.05~40Hz(-3.0dB~+0.4dB)

CMRR: Monitoring:  $> 105$ dB  
Diagnosis:  $> 90$ dB  
Surgery:  $> 105$ dB  
ST:  $> 105$ dB

Input Impedance:  $\geq 5$ M $\Omega$

Input signal range:  $\pm 8$ mV

HR trigger threshold 200 $\mu$ V

Lead off detection  
Measuring electrode:  $< 0.1$  $\mu$ V  
Driving electrode:  $< 1$  $\mu$ V

Pacemaker pulse suppression switch: Manual selection when the pacemaker is turned on

Analog output: Magnification: 1:1000;  
Accuracy:  $\pm 5\%$   
Bandwidth: 0.5Hz ~ 40Hz  
Delay:  $\leq 35$ ms

ST Detection: -2.0mV ~ +2.0mV (-20.0mm ~ +20.0mm)

Resolution: 0.01mV

Accuracy: -0.8mV ~ +0.8mV:  $\pm 0.02$ mV or  $\pm 10\%$ ;  
Others: Unspecified

ST analysis review 20 groups

System noise: Less than 25 $\mu$ V

Calibration voltage 1 mV; Accuracy:  $\pm 5\%$

Arrhythmia Analysis: 26 Types

Pacemaker detection: Detectable

**ECG (paddle)**

Lead Type: Single lead ECG

Heart Rate measurement & alarm range: Adult: 15~300bpm  
Pediatric: 15~350bpm

Resolution: 1 bpm

Accuracy:  $\pm 1\%$  or  $\pm 1$ bpm (whichever is greater)

Bandwidth: Defib: 1~20Hz (-3dB~+0.4dB)

CMRR: Defib:  $> 105$ dB

Input Impedance:  $\geq 5$ M $\Omega$

Input signal range:  $\pm 8$ mV

HR trigger value 200 $\mu$ V

Arrhythmia Analysis: 5 Types, ASY, VF, VT, PNC, and PNP

**Respiration**

Method: Thoracic Impedance Method

RR measurement range: Adult: 0~120bpm  
Pediatric: 0 ~150bpm

Accuracy: 7~150bpm:  $\pm 2$ bpm or  $\pm 2\%$  (whichever is greater)  
0~6bpm: unspecified

Apnea Alarm: Adult: 10s~60s Ped: 10s~40s

Accuracy:  $\pm 5$ s

Alarm: Audible and visual alarm; alarm events reviewable

**COMEN NIBP**

Method Automatic oscillometric

Work mode: Manual / Automatic/Continuous

Interval Time: Adjustable  
1/2/2.5/3/4/5/10/15/30/60/90/120/180/240/480/720 min  
Continuous: 5min  
Adu/Ped: 120s

Maximum measurement cycle

Measurement Unit: mmHg / kPa selectable

Pressure types: Systolic, Diastolic, Mean

Range of systolic pressure: Adult Mode: 5.3~36kPa (40~270mmHg)  
Pediatric Mode: 5.3~26.7kPa (40~200mmHg)



Range of diastolic pressure: Adult Mode: 1.3~28.7kPa (10~215mmHg)  
Pediatric Mode: 1.3~20kPa (10~150mmHg)

Range of mean pressure: Adult Mode: 2.7~31.3kPa (20~235mmHg)  
Pediatric Mode: 2.7~22kPa (20~165mmHg)

Over pressure protection: Adult: 39.6kPa (297mmHg)  
Pediatric: 32kPa (240mmHg)  
Tolerance:  $\pm 0.4$ kPa ( $\pm 3$ mmHg)

Accuracy:  $\pm \pm 0.667$ kPa ( $\pm 5$ mmHg), if exceeds the above range, the monitor can still display normally, but the accuracy is not considered

Alarm limit: Same as the range of measurement

PR from NIBP: 40~240bpm

Resolution: 1bpm

Accuracy:  $\pm 3\%$  or  $\pm 3$ bpm, whichever is greater

### SunTech NIBP

Regulatory compliance: YY 0670-2008

Initial inflation range: Adult: 16~37.3kPa (120~280mmHg)  
Pediatric: 10.7~22.7kPa (80~170mmHg)

Maximum measurement cycle: Adult: 130s  
Pediatric: 90s

Over pressure protection: Adult/Pediatric: 40.0kPa (300mmHg)

Static pressure measurement range: 0kPa~40.0kPa (0mmHg~300mmHg)

Resolution:  $\pm 0.4$ kPa ( $\pm 3$ mmHg)

Range of systolic pressure: Adult: 5.3~34.7kPa (40~260mmHg)  
Pediatric: 5.3~21.3kPa (40~160mmHg)

Range of diastolic pressure: Adult: 2.7~26.7kPa (20~200mmHg)  
Pediatric: 2.7~16kPa (20~120mmHg)

Range of mean pressure: Adult: 3.5~29.3kPa (26~220mmHg)  
Pediatric: 3.5~17.7kPa (26~133mmHg)

PR from NIBP: 30~220bpm

Accuracy:  $\pm 2\%$  or  $\pm 3$ bpm, whichever is greater

### Nellcor SpO<sub>2</sub>

Measurement range: 0~100%

Resolution: 1%

Accuracy:  $\pm 2\%$  (70~100%, Adu/Ped, non-motion)  
1~69% unspecified

Alarm range: 20~100%

PR Measurement

Range: 20~300bpm

Resolution: 1bpm

Accuracy:  $\pm 3$ bpm (20~250bpm)  
Unspecified (251~300bpm)

Alarm range: 20~350bpm

### MASIMO SpO<sub>2</sub>

Measurement & alarm range: 1~100%

Resolution: 1%

Accuracy:  $\pm 2\%$  (70~100%, Ped/Adu, non-motion)  
 $\pm 3\%$  (70~100%, motion);  
1~69% unspecified

Alarm range: 1~100%

PR Measurement

Range: 25~240bpm

Resolution: 1bpm

Accuracy:  $\pm 3$ bpm (non-motion)  
 $\pm 5$ bpm (motion);

Alarm range: 20~350bpm

PI value: 0.02~20%

Resolution: 0.01% (0.02~9.99%)  
0.1% (10~20%)

SIQ: Available

### COMEN SpO<sub>2</sub>

Measurement & alarm range: 0~100%

Resolution: 1%

Accuracy:  $\pm 2\%$  (70~100%, Ped/Adu, non-motion)  
0~69% unspecified

PR Measurement

Range: 20~254bpm

Resolution: 1bpm

Accuracy:  $\pm 2$ bpm



Alarm range:	20~350bpm	± 5% of reading (41 – 70mmHg)
PI value:	0.05~20%	± 8% of reading (71 –100mmHg)
Resolution:	0.01% (0.05%~9.99%)	± 10% of reading (101~150mmHg)
	0.1% (10.0%~20.0%)	(In 25 °C, if RR > 80rpm, accuracy is 12% of reading)
Accuracy:	unspecified	
SIQ:	Available	CapnoTrak:

**MASIMO EtCO<sub>2</sub> (Sidestream)**

Measurement range:	0~190mmHg, 0~25vol% (at 760mmHg)	± 2mmHg (0~38mmHg)	± 10% of reading (38~99mmHg)
Accuracy:	Standard environment 22 ± 5 °C, 1013 ± 40kPa:	RR influence to EtCO <sub>2</sub> (0~99mmHg):	-2~0.5mmHg (0-40bpm)
	a) 0~114mmHg: ± (1.52mmHg+reading × 2%)	(-6% of reading)~0.5mmHg (41-70bpm)	
	b) 114~190mmHg: not defined	(-14% of reading)~0.5mmHg (71~100bpm)	
	All environment:		
	a) 0~114mmHg: ± (2.25mmHg+reading × 4%)	Resolution:	1mmHg
	b) 114~190mmHg: not defined	awRR range	Loflow: 2~150rpm
Resolution:	1mmHg or 0.1% or 0.1kPa	awRR accuracy:	CapnoTrak: 0, 2~100rpm ±1rpm
awRR range:	0~150rpm		
awRR accuracy:	±1rpm		
Response time:	< 3 s		

**Respironics EtCO<sub>2</sub> (Sidestream)**

Measurement range:	Loflow: 0~150mmHg, 0~19.7%, (0~20kPa) (at 760mmHg)
	CapnoTrak: 0~99mmHg, 0~13.03%, 0~13.2kPa (at 760mmHg)
Accuracy:	Loflow: ± 2mmHg (0~40mmHg)

**\*Notice: Specifications subject to changes without prior notice.**