



Blood and Infusion Warmer

Multiple Temperature Control
Different Kinds Heating Profile
High Accuracy

More User Friendly

Blood and Infusion Warmer Specification

Item	Specification
Temperature Setting	°C: 32°C~42.0°C; °F: 86.9°F~107.6°F
Temperature Deviation	°C: $\leq \pm 1^\circ\text{C}$; °F: $\leq \pm 1.8^\circ\text{F}$
Temperature Increment	°C: 0.1°C; °F: 0.2°F
Optional Unit	°C, °F
Warming Up Time	<4min
Overheat Protection	50±5°C, hardware and software protection
Alarm	Overheat, low temperature, system error, over time, warming up alarm
Blood/IV Sets	Standard single use PVC blood/IV tubes (diameter: 3.5-7mm, applied different heating profiles)
Display	46x72mm
Heating Way	Dry silicone heating profile
Mute Time	2mins

Item	Specification
Heating Profiles	IV tubes with diameter 3.5-7mm connection to heating profile 60, 90,100,120,140cm optional
Heating Time	00h00min~99h59min
Power Supply	100~240V,50/60HZ
Power Consumption	60VA
Operation Environment	Temp.: +5°C~+30°C; Relative Humidity: 20%~93%; Atmosphere: 70.0kPa-106.0kPa
Transportation and Storage Environment	Temp.: -20°C~+55°C; Relative Humidity: 10%~95%; Atmosphere: 50.0kPa-106.0kPa
Degree of Protection against Ingress of Liquids	IPX4
Degree of Protection against Electric Shock	Class II, Type CF
Working Mode	Continuous heating
Dimension	140*110*170mm
Weight	0.86kg (1pc 120cm heating profile included)

Blood and Infusion Warmer Features

Blood and Infusion Warmer is to warm the blood or fluid and to relieve the patient's hyperthermia; it is widely used before operation, during operation and after operation in ICU, NICU, Pediatric Dept., Emergency Dept., and Outpatient Dept., for heating blood or infusion. Different kinds detachable heating profiles, direct interface and simple operation makes it user friendly.

- | | |
|--|---|
| • Multiple Temperature Control Protection Technology | Hardware and software temperature control protection to ensure the effective and safe heating. |
| • Medical Heating Silicone Heating Profile | The heating profile makes the heat reach the patient directly and effectively. |
| • Different Kinds Heating Profiles | IV tubes with diameter 3.5, 5, 7mm connection to heating profile 60, 90,100,120,140cm optional. |
| • Dry Heating | Dry flow process, easy installation, fast heating. |
| • Display | Display the preset temp., heating temp., time, alarm message, working status. |



* The specification will be changed without prior notice, please be subject to the real features.